

### PDS Serie T PDS Benchtop Gantry

## POLY DISPENSING SYSTEMS

122, Chemin de la Cavée - 78630 Orgeval • contact@polydispensing.com • Tel : 01.39.62.40.92 www.polydispensing.com

#### PDS Serie T Benchtop Gantry

An innovative and modular dispensing robot, the PDS Serie T is a versatile system that can be used either as a desktop or a gantry system, allowing users to create their workstation.

The strength of the PDS Serie T lies in its ability to create its own working area, enabling the system to be mounted to any work surface. The system is suitable for use on any type of platform requiring a gantry type mounting with open access under the robot. It is also ideal for conveyor fed automation or can be installed in work cells operating as a slave robot.

Poly Dispensing Sysytems's new robot is ideal for form-in-place gaskets, adhesives, potting, coating and filling. The robot comprises a control module, a teach-pendant and an articulated-gantry. The PDS Serie T has a working area of 8" x 8" (200 x 200mm) with a resolution accuracy of 0.001mm. Using the teach pendant, the dispensing robot supports PDS's industry leading dispensing software and can store and retrieve up to 100 programs (400,000 points).



### DATA SHEET PDS Benchtop robot serie T

#### Features

- Ideal for form-in-place gaskets, adhesives, potting, coating and filling
- Place-anywhere PDS Serie T gantry design, allows flexible operation
- High resolution 0.001mm
- Performs continuous path and point-to-point motions
- Quick fluid-purge button located on front panel of controller
- Software tip alignment routine for quick program offsets when changing dispensing tips
- Step-and-repeat functions program one object only for multiple identical objects
- On board 100 programs, 400,000 point memory capacity, 4,000 points per program
- Available without Teach Pendant for multiple installations
- USB connector allows system updates and program interchange between robots

### **Specifications**

XYZ Robot Working Area/ mm :	200 / 200 / 50
Total load - Z axis :	Зkg
Max. Speed X&Y / Z (mm/sec) :	0.1-500 / 300
Repeatability :	+/-0.01mm/ Axis
Resolution :	0.001mm/ Axis
Data Memory :	100 programs, 4000 points/program
Motor system :	Micro stepping motor
Motion Control :	PTP & CP
Programming Method :	Teach Pendant
I/O Signals Ports :	8 Inputs / 8 Outputs
External Control Interface :	RS232
Power Supply :	AC110~220V 150W
Dimensions (WxDxH) mm :	350 x 330 x 475
Robot Weight :	23 kg

#### Poly Dispensing Systems



FRANCE - SWITZERLAND NORTH AFRICA Poly Dispensing Systems 122, Chemin de la Cavée 78630 Orgeval FRANCE + 33 (0)1 39 62 40 92 + 33 (0)1 39 62 40 94 www.polydispensing.com

BELGIUM- HOLLANDE LUXEMBOURG Gentec Benelux Rue de L'Industrie, 12 B-1400 Nivelles BELGIUM C +32 2 351 1800 +32 2 351 1962 www.gentec-benelux.com PDS S.A.S is a french company providing a wide range of dispensing equipments, proven and effective.

Distributed in over 20 countries around the world, these equipements provide tailored solutions to many users such as to improve technically their manufacturing and reduce their production cost.

All of our collaborators and sales engineers have strong technical competences. They will be able to answer your questions and offer you, after analysis, the right solution for your particular need.

- NON CONTRACTUAL DOCUMENT -

# POLY DISPENSING SYSTEMS

122, Chemin de la Cavée - 78630 Orgeval • contact@polydispensing.com • Tel : 01.39.62.40.92 www.polydispensing.com